

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 March 2001 (08.03.2001)


PCT

(10) International Publication Number  
**WO 01/17168 A2**

- (51) International Patent Classification<sup>7</sup>: H04L 12/00 (74) Agent: LEROY, T., Rahn; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).
- (21) International Application Number: PCT/US00/24072
- (22) International Filing Date: 31 August 2000 (31.08.2000) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/151,665 31 August 1999 (31.08.1999) US
- (71) Applicant (*for all designated States except US*): BROADCOM CORPORATION [US/US]; 16215 Alton Parkway, Irvine, CA 92618-3616 (US).
- (72) Inventors; and (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (75) Inventors/Applicants (*for US only*): DENNY, Lisa, V. [US/US]; 3550 Corporate Way, Duluth, GA 30096 (US). HEBSGAARD, Anders [DK/US]; 3550 Corporate Way, Duluth, GA 30096 (US). LEE, Robert, J. [US/US]; 3550 Corporate Way, Duluth, GA 30096 (US).
- Published:  
— Without international search report and to be republished upon receipt of that report.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR THE REDUCTION OF UPSTREAM REQUEST PROCESSING LATENCY IN A CABLE MODEM TERMINATION SYSTEM



(57) Abstract: Upstream requests such as a bandwidth request, are processed by CMTS out of order on a priority basis to reduce latency in responding to the request. Specifically, a cable modem termination system (CMTS) is connected to a plurality of cable modems by a cable plant. The CMTS has a burst receiver adapted to be connected to the cable plant to process upstream data packet units and bandwidth requests transmitted by the cable modems. Each packet includes a header that uniquely distinguishes the bandwidth requests from other data types. Packet data units are arranged in a first memory queue. Bandwidth requests are arranged in a second memory queue. The headers of the packets processed by the burst receiver are inspected as they arrive at the CMTS to determine if the packets are packet data units or bandwidth requests. Packet data units are routed to the first memory queue. Bandwidth requests are routed to the second memory queue. Bandwidth allocation MAP messages are generated from the bandwidth requests stored in the second queue and transmitted downstream to the cable modems. The packet data units stored in the first queue are coupled to a data output for further distribution.

WO 01/17168 A2



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

1  
METHOD AND APPARATUS FOR THE REDUCTION OF UPSTREAM REQUEST  
PROCESSING LATENCY IN A CABLE MODEM TERMINATION SYSTEM

5  
CROSS-REFERENCE TO RELATED APPLICATION(S)

This application claims priority of provisional patent application Serial No. 60/151,665, filed on August 31, 1999, the disclosure which is incorporated fully herein by reference.

10  
BACKGROUND OF THE INVENTION

This invention relates to TDMA communication systems, and more particularly, to a method and apparatus for processing bandwidth requests in a cable modem termination system (CTMS).

15 A CMTS processes various types of upstream data it receives from cable modems attached to a hybrid fiber cable (HFC) plant. Included data types are protocol data units (PDU) and requests from the cable modems for bandwidth, i.e., time slots, to transmit packet data units upstream to the CMTS. Each  
20 data type is uniquely identified in a header transmitted as part of the data packets. Conventionally, a CTMS processes all the data types in the order of receipt, irrespective of the data type.

25 SUMMARY OF THE INVENTION

According to the invention, some data types, particularly bandwidth requests, are processed out of order on a priority basis to reduce latency in allocating bandwidth to requesting cable modems. Specifically, a cable modem termination system  
30 (CMTS) is connected to a plurality of cable modems by a cable plant. The CMTS has a burst receiver adapted to be connected to the cable plant to process upstream data packet units and bandwidth requests transmitted by the cable modems. Each packet includes a header that uniquely distinguishes the bandwidth  
35 requests from other data types.

1

Data packet units are arranged in a first memory queue. Bandwidth requests are arranged in a second memory queue. The headers of the packets processed by the burst receiver are inspected as they arrive at the CMTS to determine if the packets are data packet units or bandwidth requests. Data packet units are routed to the first memory queue. Bandwidth requests are routed to the second memory queue. Bandwidth allocation MAP messages are generated from the bandwidth requests stored in the second queue and transmitted downstream to the cable modems. The data packet units stored in the first queue are coupled to a data output for further distribution.

As a result, bandwidth requests can be processed out of order and ahead of the data packet units so as to reduce latency in the allocation of bandwidth to the cable modems.

#### DESCRIPTION OF THE DRAWINGS

The features of a specific embodiment of the best mode contemplated of carrying out the invention are illustrated in the drawings, in which:

FIG. 1 is a schematic diagram of a cable transmission system including a headend with a cable modem termination system connected by a hybrid fiber coaxial (HFC) network to a plurality of cable modems;

FIG. 2 is a schematic diagram of the headend and a cable modem in one home of the cable transmission system shown in FIG. 1;

FIGS. 3 and 4 are diagrams of formats of bandwidth requests according to the DOCSIS standard;

FIG. 5 is a functional block diagram illustrating how bandwidth requests are processed according to the principles of the invention; and

FIG. 6 is a schematic block diagram of a CMTS that incorporates the invention.

1

## DETAILED DESCRIPTION OF THE SPECIFIC EMBODIMENTS

5 The disclosure of patent application Serial No. 09/574,558, filed on May 19, 2000 is incorporated fully herein by reference.

10 In a cable modem system, a headend or cable modem termination system (CMTS) is located at a cable company facility and functions as a modem which services a large number subscribers. Each subscriber has a cable modem (CM). Thus, the cable modem termination system must be capable of facilitating bidirectional communication with any desired one of the plurality of cable modems.

15 As used herein, the cable modem termination system (CMTS) is defined to include that portion of a headend which effects communication with a plurality of cable modems. A typical cable modem termination system includes a burst receiver, a continuous transmitter and a medium access control (MAC).

20 The cable modem termination system communicates with the plurality of cable modems via a hybrid fiber coaxial (HFC) network, wherein optical fiber provides communication to a plurality of fiber nodes and each fiber node typically serves approximately 500 to 2,000 subscribers. These subscribers  
25 communicate with the node via a shared coaxial cable. It is this sharing of the common coaxial cable which necessitates that the number of cable modems attached thereto be limited so as to mitigate the likelihood of undesirable bit rate reductions which inherently occur when an excessive number of cable modems  
30 communicate simultaneously over a single coaxial cable.

The hybrid fiber coaxial network of a cable modem system utilizes a point-to-multipoint topology to carry out communication between the cable modem termination system and the plurality of cable modems. Frequency domain multiple access  
35 (FDMA)/time division multiplexing (TDM) is used to facilitate

1

communication from the cable modem termination system to each of the cable modems, i.e., in the downstream direction. Frequency domain multiple access (FDMA)/time domain multiple access (TDMA) is used to facilitate communication from each cable modem to the cable modem termination system, i.e., in the upstream direction.

The cable modem termination system includes a downstream modulator for facilitating the transmission of data communications therefrom to the cable modems and an upstream demodulator for facilitating the reception of data communications from the cable modems.

Typically, the downstream modulator of the cable modem termination system utilizes either 64 QAM or 256 QAM in a frequency band of 54 MHz to 860 MHz to provide a data rate of up to 56 Mbps. Since the upstream channel has a much lower data rate requirement, the upstream demodulator typically uses either QPSK or 16 QAM in a frequency range of 5 MHz to 42 MHz to provide a data rate of up to 10 Mbps.

The asymmetric data throughput defined by the upstream channel requiring a much lower data rate than the downstream channel results from the inherently larger amount of data which is communicated via the downstream channel during pay-per-view, Internet access and the like, wherein a video signal is communicated via the downstream channel, while only control signals such as those associated with viewing of the video signal are communicated via the upstream channel. Thus, the downstream channel requirement may exceed 1.5 Mbps, while the upstream channel requirement may be as low as 16 Kbps.

In the future, it is expected that cable transmission in the upstream direction will become broader band, because digital television transmission requires less bandwidth than analog television transmission.

Each cable modem includes an upstream modulator for

1

transmitting data to the cable modem termination system and a downstream demodulator for receiving data from the cable modem termination system. The upstream modulator of each cable modem uses either QPSK or 16 QAM within the 5 MHz to 42 MHz bandwidth of the upstream demodulator and the downstream demodulator of each cable modem utilizes either 64 QAM or 256 QAM in the 54 MHz to 860 MHz bandwidth of the downstream modulator (in North America).

Contemporary cable modem systems operate on a plurality of upstream channels and utilize time division multiple access (TDMA) in order to facilitate communication between a plurality of cable modems and a single cable modem termination system on each upstream channel. Typically, between 250 and 500 cable modems communicate with a single cable modem termination system on a given upstream channel.

In order to accomplish TDMA for upstream communication, it is necessary to assign time slots within which cable modems having a message to send to the cable modem termination system are allowed to transmit. The assignment of such time slots is accomplished by providing a request contention area in the upstream data path within which the cable modems are permitted to contend in order to place a message which requests additional time in the upstream data path for the transmission of their message. (Small data packets are sometimes also transmitted in contention regions.) The cable modem termination system responds to these requests by assigning time slots to the cable modems making such a request, so that as many of the cable modems as possible may transmit their messages to the cable modem termination system utilizing TDMA and so that the transmissions are performed without undesirable collisions.

Because of the use of TDMA, the cable modem termination system must use a burst receiver, rather than a continuous receiver, to receive data packets from cable modems via upstream

1

communications. As those skilled in the art will appreciate, a continuous receiver can only be utilized where generally continuous communications (as opposed to burst communications as in the present invention) are performed, so as to substantially maintain timing synchronization between the transmitter and the receiver, as is necessary for proper reception of the communicated information. During continuous communications, timing recovery is a more straightforward process since signal acquisition generally only occurs at the initiation of such communications. Thus, acquisition is generally only performed in continuous receivers once per continuous transmission and each continuous transmission may be very long.

However, the burst communications inherent to TDMA systems require periodic and frequent reacquisition of the signal. That is, during TDMA communications, the signal must be reacquired for each separate burst transmission being received.

Since continuous receivers generally only acquire the signal once, the need to minimize acquisition time is much less critical in continuous receivers than in burst receivers, wherein acquisition must be performed for each separate burst, and therefore occurs quite frequently. Thus, there is a strong motivation to minimize acquisition time in burst receivers, so as to enhance overall data transmission efficiency and throughput. As such, it is beneficial to provide techniques which enhance the speed at which data packets transmitted according to TDMA methodologies may be acquired by a burst receiver, such as that of a cable modem termination system.

Referring now to FIG. 1, a hybrid fiber coaxial (HFC) network 10 transmits data between a headend 12, which includes at least one cable modem termination system, and a plurality of homes 14, each of which contains a cable modem. Such hybrid fiber coaxial networks are commonly utilized by cable providers



1

to provide Internet access, cable television, pay-per-view and the like to subscribers.

5 Approximately 500 homes 14 are in electrical communication with each node 16, 34 of the hybrid fiber coaxial network 10, typically via coaxial cable 29, 30, 31. Amplifiers 15 facilitate the electrical connection of the more distant homes 14 to the nodes 16, 34 by boosting the strength of the  
10 electrical signals so as to desirably enhance the signal-to-noise ratio of such communications and by then transmitting the electrical signals over coaxial conductors 30, 31. Coaxial conductors 29 electrically interconnect the homes 14 with the coaxial conductors 30, 31, which extend between amplifiers 15  
15 and nodes 16, 34.

Each node 16, 34 is electrically connected to a hub 22, 24, typically via an optical fiber 28, 32. The hubs 22, 24 are in communication with the headend 12, via optical fiber 20, 26. Each hub is typically capable communicating with approximately  
20 20,000 of homes 14.

The optical fiber 20, 26 extending intermediate the headend 12 and each hub 22, 24 defines a fiber ring which is typically capable of communicating between approximately 100,000 of homes 14 and the headend 12.

25 The headend 12 may include video servers, satellite receivers, video modulators, telephone switches and/or Internet routers 18, as well as the cable modem termination system. The headend 12 communicates via transmission line 13, which may be a T1 or T2 line, with the Internet, other headends and/or any  
30 other desired device(s) or network.

Referring now to FIG. 2, a simplified block diagram shows the interconnection of the headend 12 and an exemplary home 14, wherein a cable modem 46 communicates with a cable modem termination system at headend 12, embodied as a line card 42,  
35 via hybrid fiber coaxial network (HFC) 10.

More particularly, a personal computer 48, disposed within the home 14, is connected via cable 11 to the cable modem 46 which communicates via coaxial cable 17 with the hybrid fiber coaxial network 10. Network 10 in turn communicates via optical fiber 20 with the line card or cable modem termination system (CMTS) 42 of the headend 12. Internet router 40 permits communication between the headend 12 and the Internet or any other desired device or network.

Reference is made to FIG. 3 for a depiction of the format of one type of MAC header according to the Data-Over-Cable Service Interface Specification (DOCSIS). Specifically, FIG. 3 depicts the format of a bandwidth request. A field 60 (FC TYPE=11) identifies the header as a bandwidth request frame. A field 61 (FC PARM=00010) specifies that it is a MAC header only, i.e., there are no following data PDU's. A field 62 (EHDR\_ON=0) signifies that it is not an extended header. A field 63 (MAC\_PARM) specifies the number of requested time slots. A field 64 (SID) identifies the cable modem making the request. The bandwidth request format is explained in more detail in Table I, which follows:

Table I

Field	Usage	Size
FC	FC_TYPE = 11; MAC-Specific Header FC_PARM[4:0] = 00010; MAC Header only; no data PDU following EHDR_ON = 0; No EHDR allowed	8 bits
MAC_PARM	REQ, total number of minislots requested	8 bits
SID	Service ID (0...0x1FFF)	16 bits
EHDR	Extended MAC Header not allowed	0 bytes
HCS	MAC Header Check Sequence	2 bytes
	Length of a REQ MAC Header	6 bytes

Reference is made to FIG. 4 for a depiction of another type of format of a MAC header according to the DOCSIS specification. Specifically, FIG. 4 depicts an extended header capable of carrying a so-called "piggy-back" bandwidth request. In this case, field 60 (FC\_TYPE=XX) identifies the header as another type of MAC frame; field 61 (FC\_PARM=XXXXX) is dependent on the header type; field 62 (EHDR\_ON=1) signifies that it is an extended header; and field 63 (MAC\_PARM) specifies the length of the extended header plus optional data PDU in bytes. The extended header format is shown in more detail in Table II, which follows:

Table II

Field	Usage	Size
FC	FC_TYPE = XX; Applies to all MAC Headers FC_PARM[4:0] = XXXXX; dependent on FC_TYPE EHDR_ON = 1; EHDR present this example	8 bits
MAC_PARM	ELEN = x; length of EHDR in bytes	8 bits
LEN	LEN = x + y; length of EHDR plus OPTIONAL data PDU in bytes	16 bits
EHDR	Extended MAC Header present this example	x bytes
HCS	MAC Header Check Sequence	2 bytes
PDU	OPTIONAL data PDU	y bytes
	Length of MAC frame with EHDR	6+x+y bytes

Extended header (EHDR) field 65 in FIG. 4 contains the data fields shown in Table III, which follows:

Table III

EH Element Fields	Usage	Size
EH_TYPE	EH element Type Field	4 bits
EH_LEN	Length of EH_VALUE	4 bits
EH_VALUE	EH element data	0-15 bytes

The various extended header types are shown in Table IV, which follows:

Table IV

EH_TYPE	EH_LEN	EH_VALUE
0	0	Null configuration setting; may be used to pad the extended header. The EH_LEN MUST be zero, but the configuration setting may be repeated.
1	3	Request: mini-slots requested (1 byte); SID (2 bytes)
2	2	Acknowledgment requested; SID (2 bytes)
3 (=BP_UP)	4	Upstream Privacy EH Element
	5	Upstream Privacy with Fragmentation EH Element
4	4	Downstream Privacy EH Element
5 (=BP_DOWN)	1	Service Flow EH Element; Payload Header Suppression Header
	2	Service Flow EH Element; Payload Header Suppression Header (1 byte)
		Unsolicited Grant Synchronization Header (1 byte)
6-9		Reserved
10-14		Reserved
15	XX	Extended EH Element: EHX_TYPE (1 byte), EHX_LEN (1 byte), EH_VALUE (length determined by EHX_LEN)

1

As shown in Tables III and IV, extended headers with piggy back bandwidth requests are designated EH\_TYPE=0001 in a field EH\_TYPE, the number of requested minislots and the requesting cable modem (SID) are contained in a field EH\_VALUE, and the length of the EH\_VALUE field is contained in a field EH\_LEN.

Reference is made to FIG. 5, which illustrates how the invention operates to process some data types, particularly bandwidth requests received, at a CMTS out of order on a priority basis to improve the quality of service of a cable modem system. Incoming data packets received by the CMTS from cable modems are fed to a storage register 70. As represented symbolically by a switch 71 and a switch control 72, a header monitor 63 reads the header of each data packet and makes a decision whether to route the data packet to a regular queue 64 or a priority queue 65. Head monitor 63 inspects header fields 60 and 62 (FIGS. 3 and 4). If FC\_TYPE=11 in field 60, the packet is a bandwidth request so the entire packet is sent to priority queue 65. If EHDR\_ON=1 in field 62 and EH\_TYPE=0001 in field 65, the packet contains a piggy-back request so the EH\_VALUE containing the number of requested minislots and the requesting cable modem (SID) and the EH\_LEN containing the length of the EH\_VALUE are sent to priority queue 65; the remainder of the header and the appended PDUs are sent to regular queue 64. Packet data units (PDU's) and messages other than bandwidth requests are identified by monitor 63 because neither of the conditions set forth in the preceding two sentences are present in the header; these data packet units are sent to regular queue 74. Regular queue 74 is coupled to a packet processing unit 76 and priority queue 75 is coupled to a bandwidth request processing unit 77, which generates bandwidth allocation MAPS for transmission downstream to the cable modems. Reference is made to application Serial No.

1

09/574,558 for a further description of the MAP generation process. In a typical embodiment of the invention, the packet and bandwidth request processing functions are performed by software.

FIG. 6 shows a CMTS at headend 12 (FIG. 2), which incorporates the functionality described in connection with FIG. 5. In a typical embodiment, the components shown in FIG. 6 within a block 100 all reside on a single integrated circuit chip and the other component shown in FIG. 6 reside off chip 100. For the purpose of illustration, four upstream data channels are shown although more could be utilized. In each upstream data channel, a burst receiver 101 is coupled by a PHI interface 102 to a prepare unit 103. Burst receivers 101 could, for example, be BCM3138 burst receivers marketed by Broadcom Corporation. As described in application Serial No.09/574,558, data is transferred between burst receivers 101 and PHY interfaces in both directions. Prepare units 103 inspect the header of each packet to determine if encryption was applied to the packet. Each prepare unit 103 is coupled by a decryptor (DES) unit 104 to a header processor 105. If encryption was applied to a packet the packet is decrypted in unit 104. A key RAM interface unit 110 is connected from DES unit 104 to U-bus 107 for this purpose. Each header processor 105 is coupled by a burst DMA unit 106 to an upstream U-bus 107. U-bus 107 is coupled by a RAM interface 108 to an external, i.e., off-chip, RAM 109, in which reassembly queues and DES keys are stored. Burst DMA unit 106 assigns addresses to data packets stored in RAM 109, checks the CRC, and adds control data to the data packets stored in RAM 109 based on the header data. It also retrieves DES keys from RAM 109 response to key RAM interface unit 110. A temporary reassembly memory engine 110 is also connected to upstream U-bus 107. Reassembly engine 110 stores the received parts of fragmented data while the fragmented data

1

is being reassembled into a PDU. Reference is made to application Serial No. 09/574,558 for a description of the fragmentation process. A PHS expansion and queue manager 111 connects upstream U-bus 107 to an upstream U-bus 112. Reference is made to application Serial No. (Attorney Docket 36887), filed on even date herewith by John D. Horton, Jr., entitled "Method and Apparatus for the Suppression of Packet Headers" for a more detailed description of the PHS expansion process. U-bus 112 is connected by a RAM interface 113 to an external RAM 114 in which PHS rules, output queues, and MIBs are stored. Reassembly unit 110 and manager 111 convert the data in the PDUs into standard ethernet format and send such data via U-bus 112 to RAM 114 until such data is called by an upstream egress engine 122.

Chip 100 has two data ports. One data port is a packet port 120 for exchanging PDUs with an ethernet network. The other data port is a PCIX bus interface unit (BUI) 121 through which data is exchanged with an external, i.e., off-chip processor (not shown). Thus, data stored in RAMs 109 and 114 is sent to and from the external processor through interface 121. The external processor performs the MAC functions described in application Serial No. 09/574,558 and in the DOCSIS specification. Upstream egress engine 122 feeds PDUs to packet port 120 and data messages to PCIX port 121 for transmission to the external processor. U-bus 107 is coupled to PCIX port 121 by a PCI-to-U-bus bridge 123 so as to form a control path between U-bus 112 and PCIX port 121. Header processors 105 are each coupled to a request FIFO DMA unit 125, which is in turn coupled by U-bus 112 to RAM 114. Unit 125 assigns addresses in RAM 114 for storage of the bandwidth requests in a queue until the bandwidth requests are sent to the external processor to generate the bandwidth allocation MAPS and sends these addresses to the external processor via bridge 123.

PCIX port 121 and packet port 120 are coupled by a

1  
downstream ingress engine 126 to a downstream U-bus 127. A RAM  
interface 128 couples U-bus 127 to an external RAM 129, which  
5 stores downstream priority queues, packet header suppression  
rules, and DES keys and to an in-band downstream queue manager  
130. Queue manager 130 is coupled by a packet header  
suppression unit 131 to a DOCSIS header creation unit 132. For  
a description of header suppression unit 131 reference is made  
10 to the previously mentioned application (attorney docket  
B600:36887). DES, CRC, and HCS are appended to the data packets  
in a unit 137. Unit 137 is coupled by a map extractor FIFO 138  
to a MPEG encapsulation unit 139 for transmission in the  
downstream in-band data channel.

15 In the usual mode of operation, upstream egress engine 122  
and downstream ingress engine 128 control the transmission of  
the data they process independent of the external processor.

A copy of the MAPs in FIFO 138 is also made for use in the  
CMTS. The MAP copies are coupled to a MAP parser and overflow  
20 interface 140, which filters out what is not needed for use in  
the CMTS, leaving only the MAP information elements (IEs) needed  
in the CMTS to process signal burst received from the cable  
modems. These IEs are fed to a MAP FIFO 142. If there are too  
many IEs to store in MAP FIFO 142, the overflow is stored  
25 temporarily in RAM 129 for later retrieval. This gives the  
processor more flexibility to generate MAPs when the processing  
time is available. MAP FIFO 142 is coupled to PHY interfaces  
102 to feed the IEs thereto. The IEs assist in identifying and  
demodulating the signal bursts received by burst receivers 101  
30 as described in application Serial No. 09/574,558. U-bus 127  
is also coupled by an SPI interface 143 to each burst receiver  
101. Burst receiver configuration information is sent through  
interface 143 to burst receivers 101 to configure them for  
receipt of data transmitted by the cable modems as described in  
35 application Serial No. 09/574,558.



1

Reference is made to application Serial No. (Attorney  
Docket 36886), filed by Anders Hebsgaard on even date herewith,  
5 entitled "Method and Apparatus for the Synchronization of  
Multiple Cable Modem Termination Systems Devices" for a detailed  
description of a plurality of CMTS chips connected together so  
the same MAP information is shared by all the CMTS chips and all  
the CMTS chips are synchronized to a master clock in one of the  
10 CMTS chips which is designated as a master CMTS. To this end,  
MAP extractor FIFO 138 is also coupled to a master/slave  
interface unit 144 to send copies of the MAPs to slave CMTS  
chips 100 (not shown). An external master clock (not shown) is  
coupled to a MUX and timestamp control unit 141, which is  
15 connected to a time stamp generation unit 145. Unit 141 is  
coupled to interface unit 144 to send time stamps to the slave  
CMTS chips to synchronize their operation to the master clock.  
Generation unit 145 is coupled to an encapsulation unit 139 to  
embed time stamps in the in-band downstream data flow.

20 An external multiplexer 146 is fed to one input of an MPEG  
multiplexer 147. Encapsulation unit 139 is fed to the other  
input of multiplexer 147. Multiplexer 147 is coupled by a  
modulator interface 148 to an external downstream modulator 149,  
which could be, for example, a BCM3034 modulator marketed by  
25 Broadcom Corporation. Other content such as graphics overlays  
could be introduced at the headend through multiplexer 146. To  
this end, multiplexer 146 is coupled to control unit 141 to  
coordinate the merger of data from multiplexer 146 with the data  
from encapsulation unit 139. Control unit 141 is connected to  
30 multiplexer 147 to control the selection of its inputs so only  
one input is transmitted to modulator interface 148. SPI  
interface 143 is also coupled to modulator 149 to supply  
configuration data thereto such as the modulation type (e.g.,  
QAM and symbol rate). Bridge 123 is coupled by an out-of-band  
35 generator 150 and a PHY interface 151 to a out-of-band

1

5

10

transmitter 152, which could be for example, a BCM3037 modulator marketed by Broadcom Corporation. SPI interface 143 is also coupled to transmitter 152 to supply configuration data thereto. Reference is made to application Serial No. (Attorney Docket 36889), filed by Thomas J. Quigley on even date herewith, entitled "Method and Apparatus for Latency Reduction in Low Power Two Way Communication Equipment Applications in Hybrid Fiber Cable Plants " for a detailed description of the out-of-band channel and its uses.

15

20

25

30

35

1

## WHAT IS CLAIMED IS:

1. A cable modem termination system (CMTS) connected to  
5 a plurality of cable modems by a cable plant, the CMTS  
comprising:

a burst receiver adapted to be connected to the cable  
plant to process upstream packets of data and bandwidth requests  
transmitted by the cable modems, each packet including a header  
10 that uniquely distinguishes the bandwidth request packets from  
the other packets;

a first memory queue in which data packets are arranged;  
a second memory queue in which bandwidth request packets  
are arranged;

15 means for inspecting the headers of the packets processed  
by the burst receiver;

means responsive to the inspecting means for routing  
data packets to the first memory queue;

means responsive to the inspecting means for routing  
20 bandwidth request packets to the second memory queue;

means connected to the second memory queue for generating  
bandwidth allocation MAP messages responsive to the bandwidth  
requests;

a transmitter adapted to be connected to the cable plant  
25 to transmit the generated bandwidth allocation MAP messages  
downstream to the cable modems;


a data output; and

means connected to the first memory queue for coupling the  
data packets to the data output circuit.

30

35

FIG. 1






FIG. 3




FIG. 4





FIG. 5







(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 March 2001 (08.03.2001)


PCT

(10) International Publication Number  
**WO 01/17168 A3**

- (51) International Patent Classification<sup>7</sup>: **H04L 12/56**
- (21) International Application Number: **PCT/US00/24072**
- (22) International Filing Date: **31 August 2000 (31.08.2000)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/151.665 31 August 1999 (31.08.1999) **US**
- (71) Applicant (for all designated States except US): **BROADCOM CORPORATION** [US/US]: 16215 Alton Parkway, Irvine, CA 92618-3616 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DENNY, Lisa, V.** [US/US]: 3550 Corporate Way, Duluth, GA 30096 (US). **HEBSGAARD, Anders** [DK/US]: 3550 Corporate Way, Duluth, GA 30096 (US). **LEE, Robert, J.** [US/US]: 3550 Corporate Way, Duluth, GA 30096 (US).
- (74) Agents: **STERNE, Robert, Greene et al.**; Sterne, Kessler, Goldstein & Fox P.L.L.C., Suite 600, 110 New York Avenue, N.W., Washington, DC 20005-3934 (US).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO** patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), **Eurasian** patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), **European** patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), **OAPI** patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- (88) Date of publication of the international search report:  
22 November 2001

[Continued on next page]

(54) Title: **METHOD AND APPARATUS FOR THE REDUCTION OF UPSTREAM REQUEST PROCESSING LATENCY IN A CABLE MODEM TERMINATION SYSTEM**



(57) Abstract: Upstream requests such a bandwidth request, are processed by CMTS out of order on a priority basis to reduce latency in responding to the request. Specifically, a cable modem termination system (CMTS) is connected to a plurality of cable modems by a cable plant. The CMTS has a burst receiver adapted to be connected to the cable plant to process upstream data packet units and bandwidth requests transmitted by the cable modems. Each packet includes a header that uniquely distinguishes the bandwidth requests from other data types. Packet data units are arranged in a first memory queue. Bandwidth requests are arranged in a second memory queue. The headers of the packets processed by the burst receiver are inspected as they arrive at the CMTS to determine if the packets are packet data units or bandwidth requests. Packet data units are routed to the first memory queue. Bandwidth requests are routed to the second memory queue. Bandwidth allocation MAP messages are generated from the bandwidth requests stored in the second queue and transmitted downstream to the cable modems. The packet data units stored in the first queue are coupled to a data output for further distribution.

WO 01/17168 A3



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No

PC /US 00/24072

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	WO 99 61993 A (MOTOROLA INC) 2 December 1999 (1999-12-02) page 1, line 21 -page 2, line 16 page 17, line 23 -page 21, line 2 page 24, line 8 -page 25, line 10 page 26, line 1 -page 28, line 15 ----	1
A	EP 0 829 986 A (LUCENT TECHNOLOGIES INC) 18 March 1998 (1998-03-18) column 1, line 11 - line 53 column 3, line 21 -column 4, line 25 ----	1
A	MICROSOFT CORPORATION: "Quality of Service and DOCSIS Networks" MICROSOFT WEBSITE, 19 August 1999 (1999-08-19), pages 1-4, XP002163751 the whole document -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*S\* document member of the same patent family

Date of the actual completion of the international search

15 June 2001

Date of mailing of the international search report

28/06/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Brichau, G

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/24072

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9961993 A	02-12-1999	AU 4315799 A BR 9910724 A EP 1082665 A	13-12-1999 30-01-2001 14-03-2001
EP 0829986 A	18-03-1998	US 6078564 A JP 10126446 A	20-06-2000 15-05-1998